106.STH

×

The One Systems 106.STH[™] is a premium-grade 6.5" two-way loudspeaker suitable for indoor and outdoor professional audio applications where high intelligibility and accuracy are required.

××

Cena: Kategorie: <u>Audio</u>, <u>Scena</u>, <u>Głośniki</u>, <u>Instalacje AV</u>, <u>Nagłośnienie obiektów</u>

OPIS

106.STH SILVER SERIES LOUDSPEAKERS

The system's direct-radiating transducers include a 6.5" woofer with a large-sized voice coil that provides high reliability and excellent linearity. Its HF section utilizes a small-format

compression driver with a Low-Q 110° x 70° waveguide. The 106.STH is installer-configurable for Lo-Z (8 ohm) or Hi-Z (70.7 / 100 volt) operation using separate input barrier strips. The 106.STH's rugged thick-walled enclosure, specially-built components and its stainless steel rigging hardware ensures long life in direct weather applications. The 106.STH U-Bracket is comprised of structural steel with a zinc powder coating. Wall and pole mount pan/tilt brackets are available for added installation flexibility.

U-Bracket is included as standard

SPECIFICATIONS:

- Frequency Response: 90Hz-20kHz
- Coverage Pattern: 110 (H) x 70 (V)
- Crossover Frequency: 1.5kHz
- System Sensitivity 1w/1m: 87dB
- Power Handling: 80w
- Input Impedance (Lo Z): 8
- Input Taps (Hi Z): 50/25/12.5w
- Weight: 5.2kg, 11.4 lbs
- Size (mm): 312 x 185 x 217.1 (Not including U-Bracket)
- Size (Inches): 12.3 x 7.3 x 8.5 (Not including U-Bracket)