



## C12



The DUAL C12 is a trapezoidal-wedged shape multipurpose speaker for use in PA systems or as an on-stage monitor that features a 12" low frequency transducer of 2.5 in VC capable of delivering excellent dynamic range, flat frequency response and a very low distortion figure which combined with 1" (1.73in VC) HF driver result in a superb sound and exceptional performance.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

## GALLERY IMAGES



## OPIS

### Key Features

- Multipurpose 2-way passive speaker
- Bass reflex trapezoidal enclosure
- 12" (2.5in VC) MF + 1" HF (1.73in VC) EU transducers

- 2x NL4 connected in parallel
- User-rotatable CD horn 90°x60° for ideal dispersion
- Ø35mm pole mount with 0° and 5° tilt
- Integrated rigging system with 3x M10 inserts
- Rugged and durable 15mm birch plywood
- Powder coated custom perforated steel grille

## TECH SPECS

Type	2-Way passive loudspeaker
Enclosure Design	Bass reflex trapezoidal
Power Output (RMS)	360W (EMS) 510W (Program) 900W (Peak)
Frequency Range	75Hz - 18kHz
Nominal Impedance	8Ohm
Transducer Type	10" MF (2in VC) EU transducer 1" HF (1.73in VC) EU transducer
Dispersion	CD horn, 90°x60° and 60°x90° User-rotatable
Crossover Frequency	2000Hz
Max. SPL (peak)	125dB @ 1m
Connector	2x NL4 in parallel
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille with acoustic foam Ø35mm pole mount with 0° and 5° tilt
Installation / Rigging / Flying	3x M8 flying points "U" bracket for horizontal and vertical installation
Dimensions (WxDxH)	320x350x550mm 12.60x13.78x21.65in



Weight	18Kg 39.68lb
--------	-----------------