

## C15



The DUAL C15 is a trapezoidal-wedged shape multipurpose speaker for use in PA systems or as an on-stage monitor that features a 15" low frequency transducer of 2.5 in VC capable of delivering excellent dynamic range, flat frequency response and a very low distortion figure which combined with 1" (1.73in VC) HF driver result in a superb sound and exceptional performance.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

## GALLERY IMAGES



## OPIS

### Key Features

- Multipurpose 2-way passive speaker
- Bass reflex trapezoidal enclosure
- 15" (2.5in VC) MF + 1" (1.73in VC) HF EU transducers

- 2x NL4 connected in parallel
- User-rotatable CD horn 90°x60° for ideal dispersion
- Ø35mm pole mount with 0° and 5° tilt
- Integrated rigging system with 3x M10 inserts
- Rugged and durable 15mm birch plywood
- Powder coated custom perforated steel grille

## TECH SPECS

Type	2-Way passive speaker
Enclosure Design	Bass reflex trapezoidal
Power Output (RMS)	410W (RMS) 560W (Program) 1100W (Peak)
Frequency Range	50Hz - 18kHz
Nominal Impedance	8Ohm
Transducer Type	15" MF (2.5in VC) EU transducer 1" HF (1.73in VC) EU transducer
Dispersion	CD horn, 90°x60° and 60°x90° User-rotatable
Crossover Frequency	2000Hz
Max. SPL (peak)	129dB @ 1m
Connector	2x NL4 in parallel
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille with acoustic foam Ø35mm pole mount with 5° tilt
Installation / Rigging / Flying	3x M10 flying points "U" bracket for horizontal and vertical installation
Dimensions (WxDxH)	430x420x690mm 16.93x16.54x27.17in



Weight	23Kg 50.71lb
--------	-----------------