

## D4K+



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Wzmacniacze mocy](#), [Instalacje AV](#),  
[Wzmacniacze mocy i procesory DSP](#)

## GALLERY IMAGES



## OPIS

### Key Features

- Professional and powerful class D amp
- High dynamic range and low distortion
- 4x 1000W, 2x 1000W + 2000W (Bridge 8ohm)
- 2x 2000W / 8ohm (Bridge)
- Status LEDs in front panel
- Front LED display showing current setup/configuration
- Electronically balanced XLR inputs, Speakon outputs

- Efficient forced-air cooling system
- Fully self-protected for SMPS and channels
- AC 100V - 240V, 50/60Hz Universal mains
- Solid construction for 19" - 3U rack mount

## TECH SPECS

Type	Class D amplifier, Powersoft modules
No. of Channels	4
RMS Power @ 8Ω / 1kHz / 0.1% THD	2x 2000W / 8ohm - BRIDGE
RMS Power @ 4Ω / 1kHz / 0.1% THD	4x 1000W, 2x 1000W + 2000W (Bridge 8ohm)
Gain	38dB (x80 voltage gain)
Signal-to-noise ratio	115dB (A weighted)
T.H.D. (20Hz - 20kHz)	< 0,09% from 0.1W to full power
Other Features	Output voltage: 150peak Output current: 54Apeak
Frequency Range	20Hz - 20kHz (±3dB) @ 1W, 8ohm
Damping Factor	> 500 @ 100Hz
Inputs	4x XLR/F 3p 4x XLR/M 3p - LINK
Outputs	4x Speakon NL4 2x Speakon NL4 red - Bridge
Indicators	Status, Clip, Protect, Bridge Front LED display showing current
Other Features	setup/configuration User-selectable through push buttons
Cooling	Fan, variable speed, temperature controlled Extensive protection circuitry: power limiters, thermmal shutdown
Protections	Short circuit, overload and clip limiter Temperature protection of transformer & heat-sinks



Power Consumption	Regulated SMPS with PFC
Operation Voltage	AC 100V - 240V, 50/60Hz
Connectors	Neutrik powerCON in, Neutrik powerCON out
Other Features	Rugged and solid steel construction, AL front panel
Other Features	Electrostatic black powder coating
Dimensions (WxHxD)	3RU - Rack 19" 4400mm depth
Weight	12Kg 26.46lb