

D8K



Cena:

Kategorie: [Audio](#), [Scena](#), [Wzmacniacze mocy](#), [Instalacje AV](#),
[Wzmacniacze mocy i procesory DSP](#)

GALLERY IMAGES



OPIS

Key Features

- Professional and powerful class D amp
- High dynamic range and low distortion
- 4x 2000W / 4ohm high power channels
- 2x 4000W / 8ohm BRIDGE
- Status LEDs in front panel
- Electronically balanced XLR inputs, Speakon outputs
- Efficient forced-air cooling system

- Fully self-protected for SMPS and channels
- AC 100V - 240V, 50/60Hz Universal mains
- Solid construction for 19" - 2U rack mount

TECH SPECS

Type	Class D amplifier, Powersoft modules
No. of Channels	4
RMS Power @ 8Ω / 1kHz / 0.1% THD	2x 4000W - BRIDGE
RMS Power @ 4Ω / 1kHz / 0.1% THD	4x 2000W
Gain	38dB (x80 voltage gain)
Signal-to-noise ratio	112dB (A weighted)
T.H.D. (20Hz - 20kHz)	< 0,05% from 0.1W to full power
Other Features	Output voltage: 135peak Output current: 52Apeak
Frequency Range	20Hz - 20kHz (±3dB) @ 1W, 8ohm
Damping Factor	> 500 @ 100Hz
Inputs	4x XLR/F 3p 4x XLR/M 3p - LINK
Outputs	4x Speakon NL4 2x Speakon NL4 red - Bridge
Indicators	Status, Clip, Protect, Bridge
Cooling	Fan, variable speed, temperature controlled Extensive protection circuitry: power limiters, thermmal shutdown
Protections	Short circuit, overload and clip limiter Temperature protection of transformer & heat- sinks
Power Consumption	Regulated SMPS with PFC
Operation Voltage	AC 100V - 240V, 50/60Hz
Connectors	Neutrik powerCON in



Other Features	Rugged and solid steel construction, AL front panel
Other Features	Electrostatic black powder coating
Dimensions (WxHxD)	2RU - Rack 19" 320mm depth
Weight	11Kg 24.25lb