

DLP12



The DUAL PRO series speaker range offers high-quality 2-way, elegant, refined and wedge shaped enclosures. Designed to deliver nothing but high performances this DLP12 incorporates 12" (3in) midbass transducers with high power handling capabilities combined with a 1.4" (2.56in) NEO driver coupled to a CD horn to ensure a precise audience coverage, improved sound quality and outstanding speech intelligibility. The dispersion of the CD horn is symmetric and rotatable 90°x60° or 60°x90° in order to keep the same coverage in case of horizontal use as the DLP enclosures offer a

x x

Cena:

monitor wedge shape in case of use as a stage monitor.

Kategorie: <u>Audio</u>, <u>Scena</u>, <u>Głośniki</u>, <u>Instalacje AV</u>, <u>Nagłośnienie obiektów</u>

GALLERY IMAGES







OPIS

Key Features

- 2-way multipurpose passive speaker
- 12" (3in VC) MB drivers with high power handling capabilities
- 1,4" (2.56in VC) Neodymiun high frequency driver
- User-rotatable CD horn 90°x60° for ideal dispersion
- Dual NL4 connectors + NL4MPR (for stage monitor)
- Elegant, refined and compact design
- Integrated rigging system, Ø35mm pole mount socket with 5° tilt
- Rugged and durable 15mm birch plywood
- Suited for FOH, High-end monitor, Frontfill systems
- Expandable with subs for a powerful front PA

TECH SPECS

Type 2-Way passive multipurpose speaker

Enclosure Design Bass reflex trapezoidal enclosure

500W (RMS)

Power Output (RMS) 780W (Program)

2000W (Peak)

Frequency Range 52Hz - 19kHz (+/-10dB)

Nominal Impedance 80hm

Transducer Type 12" MF (3in VC) EU transducer

1.4" Neodymium HF (2.56in VC) EU transducer

CD horn, 90°x60° and 60°x90°

Dispersion User-rotatable

Crossover Frequency 1200Hz

Max. SPL (peak) 127dB @ 1m

Connector 2x NL4 in parallel

1x NL4MPR for stage monitor

Construction 15mm brich plywood, textured polyurea coating

Grille Custom perforated metal grille with acoustic foam

Ø35mm pole mount with 5° tilt

Installation / Rigging / Flying 5x M8 flying points

Wallmount bracket available

370x350x630mm Dimensions (WxDxH)

14.57x13.78x24.80in

28Kg Weight

61.73lb