
Presentation:


The BASS series offers a professional and compact passive and active subwoofers range becoming the perfect choice for sound reinforcement challenges demanding high SPL and natural sounding bass response designed to enhance the ultra-low bass of an existing PA system.

This G218 is built on a Reflex Loaded design equipped with 2x 18" (4in) LF transducers capable of delivering 2400W AES (9600W peak), chosen to provide clean, undistorted low frequency reproduction at very high sound pressure levels and able to withstand high power levels without damage.


To ensure a perfect matching and avoid undesired vibrations during high SPL operation the enclosures are constructed in 18mm reinforced birch plywood with a rugged and durable polyurea coating.

The ergonomic carrying handles permit a secure grip from all sides and convenient transport and all models are prepared to accept 4 swivel castors with 16x M6 inserts on the back. Punch and bass sensation do not have to be incompatible factors and this BASS series truly is a great example.













Dimensions in mm [in]

Features:

- Reflex Loaded subwoofer
- 2x 18" (4in VC) LF EU transducer
- 2400W AES / 9600W Peak power
- 2x NL4 connected in parallel
- Versatile, compact and coherent subwoofer
- Made for an impact bass
- Recesses on the top to facilitate the stacking
- Rugged and durable 18mm birch plywood construction
- Powder coated custom perforated steel grille

Technical specifications:

Acoustical

Compact passive subwoofer Type

Enclosure design Reflex loaded Power rating (RMS/Peak) 2400W / 9600W Frequency range 27 - 180Hz (-10dB)

Nominal impedance

Transducer type 2x 18" LF (4in VC) EU transducer Crossover frequency 30Hz Butterworth 18dB (low cut filter)

SPL (1W/1kHz) 140dB @ 1m

2x NL4 speakon parallel-connected Connector

Mechanical

Enclosure 18mm birch plywood, rugged polyurea coating Grille Custom perforated metal grilles w/ acoustic foam

Color Black or white textured Hardware 4 wooden feet, 4 side handles 4 swivel castors (optional)

Prepared for stacking Dimensions 1070x830x580mm | 42.13x32.68x22.83in

Weight 93Kg | 205.03lb PROFACTOR S.A. reserve the right to change the specification in materials or designs of its products without