



I205



The I205 is a versatile 2-way high performance yet very compact and low profile loudspeaker suited for a wide range of pro audio applications. This speaker features 2x 5" (1.26in VC) rubber surround LF transducers made from copper wire that assures linearity and consistent power handling and a 1" (0.98in VC) HF driver that coupled to a 60°x60° constant directivity horn provides even coverage and uniform dispersion throughout the intended usage area. Moreover this combination exhibits smooth power response resulting in extremely natural voicing, exceptional clarity for speech and program reproduction and increased lower bass extension.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

Key Features

- Compact passive 2-way speaker
- High performance, low profile elegant design
- Front loaded enclosure
- 2x 5" (1.26in VC) rubber surround MF EU transducer
- 1" (0.98in VC) HF EU transducer
- Constant directivity 60°x60° horn
- 2x NL4 connected in parallel
- Integrated M8 threaded nuts for U-brackets (H&V)
- Ø35mm pole mount adapter (PMA205), tilt adjustment
- Rugged and durable 15mm birch plywood
- Powder coated custom perforated steel grille

TECH SPECS

TECH SPECS

Type	2-way passive speaker
Enclosure Design	Front loaded
Power Output (RMS)	200W (AES)
	280W (Program)
	380W (Peak)
Frequency Range	65Hz - 20kHz (-10 dB)
Nominal Impedance	4Ohm MF
	8Ohm HF
Transducer Type	2x 5" MF (1.26in VC) rubber surround EU transducer
	1" (1.0in VC) HF EU transducer
Dispersion	60°x60° (HxV)
Crossover Frequency	2500Hz
Max. SPL (peak)	122dB



Connector	Speakon NL4 in/out, parallel-connected
Construction	15mm birch plywood, textured polyurea coating
Grille	Custom perforated metal grille w/ acoustic mesh
Installation / Rigging / Flying	8x M8 inserts for "U" brackets, WB205H and WB205V Ø35mm pole mount adapter, PMA205
Dimensions (WxDxH)	170x230x430mm 6.69x16.93x9.06in
Weight	7.5Kg 16.54lb