

## IB12



The series comprises 3 models, IB 8 with a 8" (1.5in VC), the IB12 with a 12" (2.95in VC) and IB15 with a 15" (4in VC) all equipped with rubber surround EU transducers to provide excellent power density in compact enclosures.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),  
[Nagłośnienie obiektów](#)

## GALLERY IMAGES



## OPIS

### Key Features

- Bass reflex installation subwoofer
- Available in passive/active versions
- 1x 12" (2.95in VC) LF EU transducer
- 500W AES / 800W Program power
- 2x NL4 connectors in parallel

- Versatile, compact to permit unobtrusive placement
- 2 recessed handles on top
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

## TECH SPECS

Type	Compact PASSIVE subwoofer
Enclosure Design	Bass reflex enclosure
Power Output (RMS)	500W (AES) 800W (Program) 4000W (Peak)
Frequency Range	38Hz - 160Hz
Nominal Impedance	8 Ohm
Transducer Type	12" (2.95in VC) LF European transducer
Max. SPL (peak)	123dB @ 1m (continuous) 129dB @ 1m (peak)
Connector	2x NL4 in parallel
Construction	15mm birch plywood with polyurea coating
Grille	Custom perforated metal grille w/ acoustic foam
Installation / Rigging / Flying	4 rubber feet 2 recessed handles on top
Dimensions (WxDxH)	460x450x360mm 18.11x17.72x14.17in
Weight	21Kg 46.30lb