

IB8



The series comprises 3 models, IB 8 with a 8" (1.5in VC), the IB12 with a 12" (2.95in VC) and IB15 with a 15" (4in VC) all equipped with rubber surround EU transducers to provide excellent power density in compact enclosures.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#), [Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

Key Features

- Bass reflex installation subwoofer
- Available in passive/active versions
- 1x 8" (1.5in VC) LF EU transducer
- 200W AES / 400 Program power
- 2x NL4 connectors in parallel

- Active version driven by class D amplifier, variable X-over frequency
- Versatile, compact to permit unobtrusive placement
- Supplied with wallmount brackets
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

| | |
|---------------------------------|---|
| Type | Compact PASSIVE subwoofer |
| Enclosure Design | Bass reflex |
| Power Output (RMS) | 200W (AES) 400W (Program) |
| Frequency Range | 40Hz - 160Hz (-10dB) |
| Nominal Impedance | 8 Ohm |
| Transducer Type | 8" (1.5in VC) LF European transducer |
| Max. SPL (peak) | 115dB @ 1m (continuous) 121dB @ 1m (peak) |
| Connector | 2x NL4 in parallel |
| Construction | 15mm birch plywood with polyurea coating |
| Grille | Custom perforated metal grille w/ acoustic foam |
| Installation / Rigging / Flying | 4 rubber feet Wallmount brackets (supplied) |
| Dimensions (WxDxH) | 400x215x400mm 15.75x8.46x15.75in |
| Weight | 11Kg 24.25lb |