



LA10



Compact vertical line array element designed to provide high performance, detailed highs and a well-defined midrange. The LA10 is a front loaded enclosure that features an internal passive crossover, prepared for bi-amp operation, having built-in premium quality EU transducers (1x 10" - 3in VC) and 1x 1.4" - 2.56 VC Neodymium HF drivers, both combinations ensuring powerful and crystal clear reproduction, high SPL with an extended frequency response. The MF/HF pattern control is array splay dependent thus offering a coverage of 100°x7° (HXV) thanks to true wave guide horn that ensure consistent and long range projection with very low distortion levels.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

Key Features

- Front loaded array element, passive
- Trapezoidal enclosure
- 10" MF (3in VC) + 1.4" HF NEO (2.56in VC) EU transducers
- 2x NL4 connected in parallel
- Bi-amp operation
- High performance and crystal clear reproduction
- Faithful dynamic response and great range
- Integrated rigging system for stacked and flown configurations
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

TECH SPECS

| | |
|---------------------|---|
| Type | 2-way line array element |
| Enclosure Design | Trapezoidal array enclosure |
| Power Output (RMS) | 600W (RMS) 780W (Program) 1500W (Peak) |
| Frequency Range | 85Hz - 20kHz (-10dB) |
| Nominal Impedance | 8Ohm |
| Transducer Type | 10" MF (3in VC) EU transducer 1.4" HF NEO (2.56in) EU transducer |
| Dispersion | Horizontal: 100° Vertical: 7° |
| Crossover Frequency | 1600Hz Bi-amp operation, user-selectable |
| Max. SPL (peak) | 128dB @ 1m |
| Connector | 2x NL4 in parallel |
| Construction | 15mm birch plywood, rugged polyurea coating |
| Grille | Custom perforated metal grille with acoustic foam |



| | |
|---------------------------------|--|
| Installation / Rigging / Flying | Integrated rigging flyware |
| | Splay angle adjustable, 8° (1° increments) |
| | Ø9.8mm ball pins w/ stainless steel lanyard with PVC |
| Dimensions (WxDxH) | 540x430x310mm |
| | 21.60x16.93x12.20in |
| Weight | 22Kg |
| | 48.50lb |