

LA28



Compact vertical line array element designed to provide high performance, detailed highs and a well-defined midrange. The LA28 is a front loaded enclosure, curvilinear array, that features an internal passive crossover, prepared for bi-amp operation, having built-in premium quality EU transducers (2x 8" - 2in VC) and 1x 1.4" - 2.56 VC Neodymium HF drivers, both combinations ensuring powerful and crystal clear reproduction, high SPL with an extended frequency response. The MF/HF pattern control is array splay dependent and horizontal coverage is 100° x array length-splay dependent (HXV) thanks to true wave guide horn that ensure consistent and long range projection with very low distortion levels.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#), [Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

Key Features

- Ultra-Compact 2-way curvilinear array module
- Exceptional pattern control due to symmetrical design
- 2x 8" (2in VC) MF + 1.4" (2.56in VC) Neodymium HF driver
- 2x NL4 connected in parallel
- Bi-amp operation
- High performance and crystal clear reproduction
- Faithful dynamic response and great range
- Integrated rigging system for ground stacking and flown configurations
- Rugged and durable 15mm birch plywood construction
- Touring sound reinforcement for small and mid-sized venues

TECH SPECS

Type	2-way curvilinear array element
Enclosure Design	Trapezoidal array enclosure
Power Output (RMS)	500W (RMS) 800W (Program) 1600W (Peak)
Frequency Range	62Hz - 19.5kHz (-10dB)
Nominal Impedance	MF: 80hm HF: 80hm
Transducer Type	2x 8" (2in VC) MF EU transducer 1.4" (2.56in VC) Neodymium HF EU transducer
Dispersion	Horizontal: 100° Vertical: array length-splay dependent
Crossover Frequency	1600Hz Bi-amp operation, user selectable
Max. SPL (peak)	128dB @ 1m
Connector	2x NL4 in parallel
Construction	15mm birch plywood, rugged polyurea coating
Grille	Custom perforated metal grille with acoustic foam



Installation / Rigging / Flying	Integrated rigging flyware Splay angle adjustable, 8° (1° increments) Ø9.8mm ball pins w/ stainless steel lanyard with PVC
Dimensions (WxDxH)	640x480x235mm 25.19x18.89x9.25in
Weight	25Kg 55.16lb