

LAB 21 HS



LAB 21 HS is a loudspeaker system suited to high-quality sound reinforcement of infra-low frequencies. It comprises a NdFeB 21" long-excursion woofer magnet (6.5" voice coil). Loading is a hybrid waveguide indirect radiation system able to completely recover low frequency sound pressure emitted from the rear of its 21" woofer, which means an increase in sensitivity of 6 dB SPL.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

In other words, with the same input voltage, this system gives an additional 6 dB over the entire low frequency band compared to the same speaker used in a closed cabinet and, on average, an additional 3 dB compared to what the same speaker would give at low frequencies if used with a horn-loaded, reflex or band-pass system. The fact that the sound is generated by two masses of air moved by a single diaphragm, greatly benefiting attack

velocity in the transitory frequencies, results in deep, very clean low frequencies.

Intended as a complete system, the LAB 21 HS ensures very high electro-acoustic transduction efficiency, thanks to its excellent integration of the mechanical and acoustic domains. The coordination of these aspects, along with the dedicated amplifier (Outline T Eleven), enables the maximum energy transfer and output power control fully respecting input signals' dynamics.

LAB 21 HS has a frequency range at -10 dB of 23 Hz to 165 Hz (maximum crossover frequency suggested: 100 Hz). Among the optionals available, a trolley ensures fast handling and efficient protection of the front of the enclosure against impacts. The black finish is in special high quality wear and weather-resistant paint. Sixteen strategically positioned integral handles facilitate handling.

Features

- Infra-Sub unit with a single 21" long excursion woofer
- Very high electro-acoustic transduction efficiency (excellent integration of the various domains: electrical, mechanical and acoustic).
- The world's most compact and lightweight subwoofer with a 21" woofer
- Extremely high SPL (147 dB peak @ 1 m).
- Deep, very clean infra-low frequencies (23 Hz), thanks to an impulse response with a very small ripple.
- Highly ingenious acoustic design that ensures top performance: a hybrid waveguide indirect radiation system able to completely recover low frequency sound pressure emitted from the rear of the unit's 21" woofer.
- Built to be used alone or in multiples, with the utmost reduction of footprint in relation to output and SPL achieved.
- Easy transport when used with mobile rigs, and fits easily into any permanent installation.
- Unrivaled extension down to very low frequencies, without any noise due to turbulence caused by air passing at high speed.
- The internally braced cabinet ensures utmost sturdiness, free from harmful sound "colouring" due to resonance; an optional trolley with sturdy smooth-running wheels facilitates transport, even on relatively uneven surfaces.
- Best application in "live" concerts of all sizes, floor mounted and combined with other units of the same type for sound reinforcement of infra-low frequencies.
- High-quality permanent installations in theatres, clubs, indoor sports arenas; an ideal

match for all Outline loudspeaker systems and vertical line arrays.

FREQUENCY RESPONSE (-10 dB)	23 Hz - 165 Hz
AVERAGE DISPERSION	Quasi-omnidirectional
IMPEDANCE	4 Ω (min 4.3 Ω)
POWER - WAES	2000 (8000 peak)
MAX SHORT-TERM SPL @ 1 m*	147 dB SPL (half-space)
LOUDSPEAKERS AND LOADING	1 x 21" NdFeB woofer, hybrid waveguide indirect radiation system
WEIGHT - SINGLE UNIT	125 kg (275.5 lb)
DIMENSIONS (Net)	Height: 726 mm (28 19/32") Width: 1126 mm (44 11/32") Depth: 820 mm (32 9/32")

* calculated using +10 dB crest-factor signal