

PD4 4" HANGING PENDANT SPEAKER



Designed to meet the needs of indoor and outdoor open-ceiling commercial applications, the Pure Resonance Audio PD4 4" full-range pendant speaker is weather-resistant, high powered and easy to install. This 70-volt ceiling pendant speaker is perfect for small restaurants, retail stores, offices, warehouses, or any other open-architecture high ceiling environment where paging, announcements or foreground and background music is required.



Cena:

Kategorie: [Audio](#), [Instalacje AV](#), [Nagłośnienie kinowe](#), [Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

4" 2-WAY INDOOR/OUTDOOR COMMERCIAL PENDANT SPEAKER FOR OPEN-CEILING ARCHITECTURAL DESIGNS

Clear Wide-Coverage

The down-firing design of the driver directs the high fidelity sound for an evenly distributed 150° wide coverage pattern.

ARCHITECTURAL DESIGN

Superb sound reproduction for exposed structure or open plenum ceiling venues where a stylish contemporary speaker blends well with the architectural design.

WEATHER-RESISTANT CONSTRUCTION

Treated drivers and two-layer, powder-coated grilles bring high-performance audio and vocal clarity to both indoor and outdoor pendant-mount sound systems.

POWER TAP TRANSFORMER SWITCH

4-pin Euroblock plug and multi-tap transformer for use with 70V/100V distributed audio loudspeaker systems.

RANGE OF APPLICATIONS

Ideal for paging, announcements, or foreground and background sound reinforcement in restaurants, retail stores, offices, warehouses, or any other open-architecture high ceiling environments.

PENDANT MOUNTING HARDWARE

Easy and secure standard pendant-mount installation with the included mounting hardware. The steel hanging and safety cables, carabiner and Fastlink locking wire joiner ensure a safe and reliable installment.

The PD4 4" Pendant Speaker

Clear and Intelligible Wide-Coverage Audio for Focused Performance

Designed to meet the needs of open-ceiling commercial applications, the Pure Resonance Audio PD4 full-range coaxial hanging pendant speaker is easy to install and high powered producing clear intelligible audio in spaces with exposed structure open-architecture ceilings. The acoustically matched 4" and 1" tweeter maximize the PD4's performance while minimizing its overall footprint. The down-firing design of the driver directs the high fidelity sound for an evenly distributed 150° wide coverage pattern. A tough weather-resistant construction with treated drivers and two-layer, powder-coated grilles bring high-performance audio and vocal clarity to both indoor and outdoor pendant-mount sound systems.

Ideal 70V Hanging Speaker Solution Built for Integration in Open-Ceiling Commercial Environments

With the addition of a 4-pin Euroblock plug and multi-tap transformer for use with 70V/100V distributed audio loudspeaker systems, the Pure Resonance Audio PD4 is easily integrated into any commercial audio application. The 2-way hanging ceiling speaker provides superb sound reproduction for exposed structure or open plenum ceiling venues where a stylish contemporary speaker blends well with the architectural design. This 70-volt pendant speaker is the perfect installed sound solution for restaurants, retail stores, open office floor plans, hotels, warehouses, big box stores, fitness centers, convention centers, conference rooms, atriums, museums, theme parks, casinos, airports or any other high ceiling environment where paging, announcements, or foreground and background sound reinforcement is required.

Fast and Easy Installation to Meet the Demands of Open-Ceiling Applications

The Pure Resonance Audio PD4 is well-equipped for an easy and secure standard pendant-mount installation with the included mounting hardware. The steel hanging and safety cables, carabiner and Fastlink locking wire joiner ensure a safe and reliable installment. The crisp sounding PD4 commercial speaker can adapt to meet the demands of any open-ceiling application.

SPECIFICATIONS

Power Handling: 25 Watts RMS; 70 Watts Peak

Frequency Response (± 3 dB): 95Hz - 20KHz

Frequency Response (± 10 dB): 65 Hz - 20 kHz

Sensitivity: 85dB 1m/1w

Impedance: 8 ohm

Peak Output: 103dB

Woofers: 4 inch Polypropylene

Tweeter: 3/4 inch Black silk

Transformer: 70.7V: 2W / 4W / 8W / 16W / 8 ohm
100V: 4W / 8W / 16W / 8 ohm

Connections: Four-pin Euroblock

Grill: Baked black aluminum

Certifications: REACH, RoHS

Dimensions (H x Dia): 7" (117.8 mm) x 5" (127 mm)

Weight: 3.4 lbs (1.54 kg)

Shipping Weight: 5 lbs (2.27 kg)