

RADIAL42



PURE public address series is a step ahead for music and speech reproduction in 100V sound reinforcement systems. With the highest sound quality and speech intelligibility, both MF elements and HF elements are placed in a way to provide a very even and smooth coverage. In fact, PURE RADIAL series are designed and constructed with both 3" and 4" transducers combined to ensure a 180° horizontal directional dispersion. Elegant aluminum enclosure to provide ultra-compact cabinets capable of delivering very high sound pressure levels in difficult acoustic spaces. All models are available in either black or white finishing and for fixed installations there is a mounting bracket C-sup available. With elegant design, PURE series is the ideal solution for short or medium range environments with demanding acoustics and long reverberation times such as churches, museums, halls, conference rooms, etc.



Cena:

Kategorie: [Audio](#), [Scena](#), [Głośniki](#), [Instalacje AV](#),
[Nagłośnienie obiektów](#)

GALLERY IMAGES



OPIS

Key Features

- Public address installation speaker
- Superb speech intelligibility
- 4x 3" (0.75in) + 2x 4" (with dome tweeter) FR transducers
- Suitable for 100V high impedance installations
- Almost 180° horizontal dispersion
- Solid and elegant aluminum profile
- Custom perforated metal grille
- Textured powder coating finishing
- Supplied with with C-sup M support for wall mount

TECH SPECS

| | |
|---------------------------------|---|
| Type | Passive installation column speaker |
| Enclosure Design | Sealed |
| Power Output (RMS) | 30W |
| Frequency Range | 100Hz - 18kHz |
| Nominal Impedance | 100V line transformer in |
| Transducer Type | 4x 3" (0.75in) FR (rubber surround) 2x 4" (1in) FR (with dome tweeter and rubber surround) |
| Dispersion | 180° x 30° (HxV) |
| Crossover Frequency | 2200Hz |
| Max. SPL (peak) | 95dB @ 1m |
| Connector | Euroblock terminal |
| Construction | Extruded aluminum profile, textured powder coating |
| Grille | Custom perforated metal grille, textured powder coating |
| Installation / Rigging / Flying | C-sup M for wall mounting (supplied) |
| Dimensions (WxDxH) | 126x115x616mm 4.96x4.53x24.25in |
| Weight | 10.5Kg 23.15lb |

