

THE NOHO CLINSTALL



Ultra-compact, IP56 Weatherproof, 2-Way Full-range Loudspeaker



Cena:

Kategorie: <u>Audio</u>, <u>Scena</u>, <u>Głośniki</u>, <u>Instalacje AV</u>, <u>Nagłośnienie obiektów</u>

GALLERY IMAGES

×



×

OPIS

Our flagship product, the Noho Ci, offers everything we've learned in a powerful, sleek, visually appealing design. Behind a matte-finish surface lies a thick rotationally molded shell with outstanding acoustic properties. A mildly trapezoidal cabinet offers two-axis flypoints and yoke mount points, plus a single stand mount socket on the bottom and rear inserts for a wall or pole mount. Three layer WeatherTech $^{\text{m}}$ grill protects the also weatherproof driver from the worst the elements can offer. 120° x 120° dispersion, high efficiency, and excellent power handling make the Noho Ci an unbeatable choice for sports audio systems, retail and

architectural installations, performance spaces, and much more.

Size: 20.8" x 15.5" x10.1"

Weight: 40 lbs

Freq. Response: 55 Hz - 18 KHz (+/- 2 dB)

Sensitivity: 99.6 dB SPL (1W/1M, swept sine)
Continuous Power: 480 Watts (based on EIA test 426B)

Max. Continuous SPL 126.4 dB SPL Dispersion: 120 x 120

Connector: 2 x Speak-On NL4MP Impedance: 8 Ohms (nominal)

LF Driver: 12" custom cone driver (coaxial)
HF Driver: 1" horn-loaded compression driver