

## TL 260Z



Public address amplifier with a power up to 300W rms. The TL260Z offers a variety of input possibilities for all kinds of connection purposes such as 4 balanced MIC inputs, 2 stereo line inputs which are switchable between MIC/LINE level and a priority MIC input (with ding-dong) performed using a 5-pin DIN connector. The output signal is available in low impedance 4-16Ohm and high impedance 100V mono output zones with terminal blocks on the rear panel and the TL260Z also features a REC and SLAVE (pre-amp) outputs in RCA connector. All control functions such as volume controls, master volume control, channel selection and a 2-band tone control are located on the front panel. It is equipped with an advanced protection circuit which protects against DC short circuit and overload when necessary.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Wzmacniacze mocy](#), [Instalacje AV](#), [Wzmacniacze mocy i procesory DSP](#)

## GALLERY IMAGES



## OPIS

## Key Features

- High quality PA amplifier
- Multizone installation PA mixer-amplifier
- 4 Microphone inputs and 1 Line input
- XLR 3p balanced, Euroblock inputs
- 4-16 ohm & constant-voltage outputs (70V and 100V)
- Independent zone control switches (six)
- Bass and Teble tone controls
- Ding-dong and Priority muting by VOX
- Built-in electronic protection circuitry
- Solid construction for 19" rack - 3U mounting

## TECH SPECS

Type	Multizone PA mixer/amplifier
Power Output (RMS)	260W
Frequency Range	50Hz - 15kHz
T.H.D. (20Hz - 20kHz)	< 1% @ 1kHz
Signal-to-noise ratio	> 90 dB @ 1 kHz
Zones	6 zones
Controls	Bass and Treble, Master, Volume for MIC and Line in
Indicators	Power on, Signal and Clip, Active zone
Inputs	Microphone, XLR/F 3p Euroblock terminals Line in
Outputs	4Ω- 16Ω, 100V line, REC
Connectors	Input: 6.3mm Jack, RCA line Output: Touch-proof binding posts
Phantom Power	+48V DC
Other Features	Ding-dong, priority MIC, MIC3/LINE3 and MIC4/LINE4 switch
Protections	Short circuit, DC protection
Operation Voltage	230V AC (factory config.), 50-60 Hz



Power Consumption	260VA
Cooling	Continuously speed fan, 120mm / 230V AC
Dimensions (WxHxD)	3RU spaces, 345mm depth (13.58in)
Weight	16Kg 35.27lb