

## TL 4Z800



Public address amplifier with a power up to 800W. The PA4Z800 features 4 independent audio inputs performed using Jack 6.5mm with individual volume control on the front panel. The output signal is available on 4 high impedance 100V mono output zones of 200W with binding-post on the rear panel. It is equipped with an advanced protection circuit which protects against DC short circuit and overload when necessary. The PA4Z800 is designed for public address installations such as supermarkets, warehouses, petrol stations, etc, where there is a need to control each zone independently.



**Cena:**

**Kategorie:** [Audio](#), [Scena](#), [Wzmacniacze mocy](#), [Instalacje AV](#), [Wzmacniacze mocy i procesory DSP](#)

## GALLERY IMAGES



## OPIS

### Key Features

- High quality PA amplifier

- Multizone installation PA amplifier
- XLR 3p balanced, Euroblock inputs
- Constant-voltage outputs (100V)
- Independent zone control (four)
- Individual volume control on the front panel
- Built-in electronic protection circuitry
- Solid construction for 19" rack - 3U mounting

## TECH SPECS

Type	Multizone PA mixer/amplifier
Power Output (RMS)	4x 200W
Frequency Range	50Hz - 15kHz
T.H.D. (20Hz - 20kHz)	< 1% @ 1kHz
Signal-to-noise ratio	> 90 dB @ 1 kHz
Zones	4 zones
Controls	Input channel volume
Indicators	Power on
Inputs	Signal in
Outputs	100V line
Connectors	Microphone, XLR/F 3p Euroblock terminals Output: Touch-proof binding posts
Other Features	Independent zone control
Protections	Short circuit, DC protection
Operation Voltage	230V AC (factory config.), 50-60 Hz
Power Consumption	800VA
Cooling	Continuously speed fan, 120mm / 230V AC
Dimensions (WxHxD)	3RU spaces, 350mm depth (13.78in)
Weight	21Kg 46.30lb

